PANCONTROL.at

Voltage and continuity testers

PAN MV-1000AD

Voltage & Continuity Tester with LED indicator 12 - 1000 V AC / DC, rotary field indication & 30 mA RCD test

- Resistance measurement from 1 Ω to 1999 Ω
- **Low voltages up to 24 V: green LEDs, dangerous voltages from 50 V: red LEDs**
- Analog LED and backlit digital LCD display
- **2-pole rotary field indication**
- **Single-pole phase testing with acoustic alarm**
- Data-Hold
- **30 mA RCD test**
- **Switchable load for suppressing stray voltages**
- **LED flashlight**
- Auto power off
- **Water and dust protection class IP 64**
- **TÜV GS tested**

Scope of delivery: protective cover, screw-contact sleeves for perfect contact in sockets, Operating manual

Technical Data	PAN MV-1000AD
DC voltage (V=)	12 - 24 - 50 - 120 - 230 - 400 - 690 - 1000 V
AC voltage (V~)	12 - 24 - 50 - 120 - 230 - 400 - 690 - 1000 V
Resistance (Ω)	1 Ω - 1999 Ω
Continuity test •)))	< 400 kΩ
Dimensions	260 x 74 x 34 mm
Weight (gross / net)	432 / 263 g
Required battery(s):	2x 1,5V AAA
Measuring category (CAT)	CAT III 1000 V / CAT IV 600 V
Accuracy (%)	3,0 % - 5,0 %

PAN MV-1000AD Video DE:

PAN MV-1000AD Video EN: