

Professional digital multimeters True RMS

PAN Profimeter-2

Digital Multimeter True RMS CAT III 600 V with Non-Contact Voltage Tester + Automatic Range Selection

- Auto range
- LCD display with bargraph 5999
- **Non contact voltage test (3 levels) (NCV)**
- **Min / Max memory**
- Relative mode (REL)
- **temperature measurement**
- Digital Display 22 mm
- **True RMS measurement**
- **Single-pole phase testing with acoustic alarm**
- Data-Hold
- Diode test
- **LED flashlight**
- Auto power off

Scope of delivery: test leads, Type-K temperature probe 40°C ~ 250°C, Operating manual



Technical Data	PAN Profimeter-2
DC voltage (V=)	10 μ V - 600 V
AC voltage (V~)	10 μ V - 600 V
DC current (A=)	0,1 μ A - 10 A
AC current (A~)	0,1 μ A - 10 A
Resistance (Ω)	0,1 Ω - 60 M Ω
Continuity test (•)))	< 30 Ω
Frequency (Hz)	0,001 Hz - 10 MHz
Duty-cycle	1 - 99 %
Capacitance (F)	10 pF - 100 mF
Temperature ($^{\circ}$ C) (type K probe)	-20 - 1000 $^{\circ}$ C
Ambient temperature ($^{\circ}$ C)	0 - 40 $^{\circ}$ C
Dimensions	166 x 78 x 48 mm
Weight (gross / net)	378 / 252 g
Required battery(s):	2x 1,5 V AAA
Measuring category (CAT)	CAT III 600 V
Accuracy (%)	0,5 % - 5,0 %



PAN Profimeter-2 Video DE:



PAN Profimeter-2 Video EN:

